

Oil and Gas Commission

6534 100th Ave, Fort St. John, B.C
V1J 8C5

APPROVAL
AA-111317

Under the Provisions of the Environmental Management Act

Coastal GasLink Pipeline Ltd.
450 1st Street SW,
Calgary, Alberta
T2P 5H1


is authorized to discharge contaminants to the environment from burn piles located along the pipeline corridor of Section 8 West of the Coastal GasLink Pipeline project, subject to the conditions listed below. Contravention of any of these conditions is a violation of the *Environmental Management Act* and may result in prosecution.

1. DEFINITIONS

For the purpose of this approval, the following definitions apply:

- 1.1. **Act** means the *Environmental Management Act*.
- 1.2. **Discharge** means the total mass of a solid, liquid or gaseous material introduced into the environment.
- 1.3. **Manager** means an OGC employee authorized to exercise the powers of the OGC under Section 15 of the *Environmental Management Act*.
- 1.4. **OGC** means the B.C Oil and Gas Commission.
- 1.5. **Approval Holder** means Coastal GasLink Pipeline Ltd.
- 1.6. **Ventilation Forecast** means the afternoon ventilation index forecast issued by Environment Canada for a geographic area.

Date Issued: January 4th, 2023



Devin Scheck, P.Ag
Supervisor, Environmental Stewardship

- 1.7. **Custom Ventilation Forecast** means a forecast of the atmosphere's ability in a geographic area to disperse smoke in accordance with section 16 of the Open Burning Smoke Control Regulation.
- 1.8. **Custom Ventilation Forecaster** means a person who a) is a meteorologist employed by environment Canada and classified as a Meteorologist 3 or above, b) is a Weather Forecaster, a Fire Weather Forecaster, an Air Quality Meteorologist or an Air Quality Science Specialist employed by or under contract with the government, or c) has similar knowledge and experience as described in a) or b) and is approved in writing by a director to conduct custom ventilation forecasts for the purposes of the Open Burning Smoke Control Regulation.

2. **AUTHORIZED DISCHARGES**

- 2.1. This subsection applies to the discharge of air contaminants from **FIVE (5) BURN PILES LOW SMOKE SENSITIVITY ZONE**. The site reference number for this discharge is E329389.

2.1.1. The approximate authorized load per pile is 3604 tonnes.

2.1.2. The authorized works are five (5) burn piles. Approximate burn pile locations are as follows:

Burn Pile	KP Location	Lat./Long.
BP 1	KP 613+550	54.05N 128.01W
BP 2	KP 616+700	54.04N 128.05W
BP 3	KP 618+100	54.04N 128.07W
BP 4	KP 619+800	54.04N 128.09W
BP 5	KP 631+750	54.07N 128.24W

2.1.3. The authorized period of discharge is up to 25 days of active burning for each pile.

2.1.4. The pile may only be ignited if the ventilation forecast for that area, obtained on the day, but before, the open burning starts is "good" or "fair" for the day the open burning starts and is "good" or "fair" for the second day of the open burning. If a custom ventilation forecast is used, the custom ventilation forecast for that area is obtained on the day before or

on the day, but before, the open burning starts, and is “good” or “fair” for the day the open burning starts and is “good” or “fair” for the second day of the open burning.

- 2.1.5. The authorized material to be combusted is blasting boxes, clean untreated wood waste including damaged rig mats, skids & wooden bridge material.
- 2.1.6. Waste which is defined in section 2 of Schedule 1 of the Waste Discharge Regulation is prohibited from being burned.
- 2.1.7. The location from which the discharge originates is within the certified pipeline project boundary.

2.2. This subsection applies to the discharge of air contaminants from **ONE (1) BURN PILE MEDIUM SMOKE SENSITIVITY ZONE**. The site reference number for this discharge is E329391.

- 2.2.1. The approximate authorized load is 3604 tonnes.
- 2.2.2. The authorized work is one (1) burn pile, the approximate burn pile location is as follows:

Burn Pile	KP Location	Lat./Long.
BP 6	Shoofly 3 KM 2.8	54.07N 128.41W

- 2.2.3. The authorized period of discharge is up to 25 days of active burning.
- 2.2.4. The pile may only be ignited if the ventilation forecast for that area, obtained on the day, but before, the open burning starts is “good” for the day the open burning starts and is “good” or “fair” for the second day of the open burning. If a custom ventilation forecast is used, the custom ventilation forecast for that area is obtained on the day before or on the day, but before, the open burning starts, and is “good” for the day the open burning starts and is “good” or “fair” for the second day of the open burning.
- 2.2.5. Ignition occurs only during the period that starts one hour after sunrise and ends 2 hours before sunset.
- 2.2.6. Material added to the ignited pile is done only during the period that starts one hour after sunrise and ends two hours before sunset.

- 2.2.7. The authorized material to be combusted is blasting boxes, clean untreated wood waste including damaged rig mats, skids & wooden bridge material.
- 2.2.8. Waste which is defined in section 2 of Schedule 1 of the Waste Discharge Regulation is prohibited from being burned.
- 2.2.9. The location from which the discharge originates is within the certified pipeline project boundary.
- 2.3.** This subsection applies to the discharge of ash produced from the combustion of wood waste authorized under this Approval.
 - 2.3.1. The authorized discharge period is continuous.
 - 2.3.2. The ash may be disposed of at a suitable disposal facility which has been authorized under the Environmental Management Act to receive industrial waste including ash from the combustion of wood waste.
 - 2.3.3. Alternatively, the ash may be disposed of on-site. The ash will be swept with a magnet to remove the metal. Once the metal is removed and the ash is cooled, the ash may be covered/buried with mineral soil. Soil handling and restoration measures will be adhered as outlined within Coastal Gaslink's Environmental Management Plan.
 - 2.3.4. On-site disposal of ash shall not occur within 100 m of a stream or permanent waterbody.
 - 2.3.5. The waste that may be discharged is the ash generated from the combustion of the authorized materials specified within Section 2.1 & 2.2.

3.0 GENERAL REQUIREMENTS

3.1 General Requirements

- 3.1.1 Nothing in the Approval authorizes an open fire that is
 - (a) prohibited by a ban on igniting open fires imposed by
 - (i) a fire department, as defined in the Fire Services Act,
 - (ii) a local government, or
 - (iii) an improvement district, as defined in the Local Government Act, or

(b) contrary to the Wildfire Act or any other enactment.

3.1.2 Despite this Approval, the Approval Holder must not start open burning or add material to the ignited piles if the local air flow or atmospheric mixing is likely to cause the smoke emitted by the open burning to

(a) negatively impact a nearby population centre or work camp,

(b) be a navigation hazard at nearby airports or on nearby highways by significantly reducing visibility.

3.1.3 Setbacks for open burning

The Approval Holder must ensure that open burning is carried out at least

(a) 500 m from all neighbouring buildings that

(i) are residences, or

(ii) contain businesses in which persons carry on the business during regular business hours, and

(b) 1000 m from the nearest property line of all schools, hospitals and community care facilities.

3.1.4 Strategies and techniques to minimize smoke

All reasonable efforts are to be taken to minimize the amount of smoke emitted by the open burning including, but not limited to;

(a) minimizing the soil content that may be mixed in with the matting

(b) construct each pile in a way that maximizes air flow

(c) use air via compressor(s) or fans to promote an efficient burn

3.1.5 Fire Protection

The burn activity will be monitored at all times until the burning is complete. Adequate fire protection equipment will be maintained on site to extinguish any fires that may ignite outside of the burn pile.

3.1.6 Cessation of Fire Feeding and Burning

The Manager may require the Approval Holder to cease the addition of material to the burn pile at any time if the Manager has reason to believe



Devin Scheck, P.Ag
Supervisor, Environmental Stewardship

that emissions from the open burning are impacting the receiving environment or when complaints are received regarding local ambient air quality.

3.1.7 Environmental Impact

Inspections of the authorized works and discharge may be carried out by OGC personnel as part of the routine inspection procedure. Based on these inspections and any other information available to the Manager on the effect of the discharge on the receiving environment, the Approval Holder may be required to undertake monitoring, additional studies, change the method of operation or shutdown the operations.

3.1.8 Disposal of Ash

The Approval Holder must take the necessary precautions for avoiding aerial dispersion of ash and the risk of ash leachate at all times.

3.1.9 Maintenance of Works and Emergency Procedures

The Approval Holder must inspect the authorized works regularly and maintain them in good working order. In the event of an emergency or condition beyond the control of the Approval Holder which prevents effective operation of the approved method of pollution control, the Approval Holder must notify the Manager immediately, and take appropriate remedial action. The Manager may reduce or suspend the operation of the Approval Holder to protect the environment until the approved method of pollution control has been restored.

Instances of approval non-compliance shall be self-disclosed upon discovery, as outlined within Chapter 3 of the OGC Compliance and Enforcement Manual; OGCWaste.Management@bcogc.ca shall also be informed of the self-disclosure.

For spills which meet the Spill Reporting Regulation reporting criteria, a report shall be made immediately to the Provincial Emergency Program telephone 1-800-663-3456.



3.1.10 Submission of Custom Ventilation Forecast

The Approval Holder must ensure that the custom ventilation forecast is submitted by email to the Ministry of Environment & Climate Change Strategy, using the email address made known by the ministry & to OGCWaste.Management@bcogc.ca before starting the open burning.

4.0 **MONITORING AND REPORTING REQUIREMENTS**

4.1 **Discharge Monitoring**

The Approval Holder must track the status of the open burning operation including the ventilation forecast or custom ventilation forecasts obtained in respect to open burning, operational hours, load frequency, approximate tonnage of material burned per day, and any fumigation issues. Daily records must be compiled and analyzed.

4.2 **Discharge Reporting**

A final report of the discharge monitoring must be submitted within 30 days after the completion of the authorized works or upon request from the OGC. Submission can be made to OGCWaste.Management@bcogc.ca.

