



March 23, 2017

9045-7400-32640-02

Ramona Stoica  
Encana Corporation  
P.O. Box 2850, 500 Centre St SE  
Calgary, AB, T2P 2S5

Dear Ms Stoica:

**RE: PRODUCED WATER DISPOSAL SPECIAL PROJECT APPROVAL, AMENDMENT #1  
ECA ECOG ETSHO b-A90-J/94-O-08; WA# 23605  
HORN RIVER FIELD – DEBOLT FORMATION**

Approval for disposal of produced water, Order 08-02-001, was issued for the subject well, Debolt formation, on February 13, 2008. The Commission is presently amending disposal well approvals to conform to current requirements.

Disposal started in May 2008, with a cumulative injected volume of 2,147,901 m<sup>3</sup> to date. Annular packer isolation testing from 2014 to 2016 shows annular wellbore integrity. The January 2016 acoustic well sounder pressure test displays a calculated reservoir pressure of 114% of initial pressure. However, confidence in this pressure test is not high due to assumptions in the methodology used to calculate the bottom-hole pressure.

Attached please find **Order 08-02-01 Amendment #1**, designating an area in the Horn River field – Debolt formation as a Special Project under section 75 of the *Oil and Gas Activities Act*, for the operation and use of a storage reservoir for the disposal of produced water. This Order contains a number of detailed operational conditions including a maximum wellhead injection pressure, reservoir pressure fill-up limit, and continuous tubing and casing pressure monitoring. Annual reservoir pressure tests are required to be performed with bottom-hole recorders to ensure accuracy of the testing. Additional general information regarding disposal wells is available on the Commission's website at <http://www.bcogc.ca/industry-zone/documentation/Subsurface-Disposal>.

The top of the disposal zone is within 100 m of the Base of Usable Groundwater as determined by the OGC. As such, a groundwater monitoring program is required to be implemented, involving the installation of a single monitoring well, to establish reference groundwater chemistry and to demonstrate consistency in groundwater chemistry over time at the monitoring well location. Specific groundwater monitoring program requirements are outlined in Appendix A.

In certain circumstances, disposal well operation may induce seismicity. The Commission advises that disposal well permit holders monitor seismic events in proximity to the well and be prepared to modify operations to mitigate induced seismicity. Permit holders may monitor seismic events through the Natural Resources Canada seismic monitoring network at <http://www.earthquakescanada.nrcan.gc.ca/recent/index-eng.php>

Should you have any questions, please contact Michelle Harding at (250) 419-4493 or the undersigned at (250) 419-4430.

Sincerely,

Ron Stefik, Eng.L.  
Supervisor, Reservoir Engineering  
Oil and Gas Commission

Attachment




### ORDER 08-02-001 Amendment #1

- 1 Under Section 75(1)(d) of the *Oil and Gas Activities Act*, the Commission designates the operation and use of a storage reservoir for the disposal of produced water, including flowback from fracturing operations, into the Debolt formation – in the Horn River field as a special project in the following area:

NTS 94-O-08 Block J Unit 90

- 2 Under section 75(2) of the *Oil and Gas Activities Act*, the special project designation in this Order is subject to the following conditions. The Permit Holder shall:

- a) Inject produced water only into the well ECA ECOG Etsho b-A90-J/94-O-08; WA# 23605 – Debolt formation (disposal perforations 678.0 – 760.0 mKB).
- b) Not exceed an injection pressure, measured at the wellhead on the subject well, of 4,045 kPag or the pressure required to fracture the formation, whichever is lesser.
- c) Inject only through tubing with a packer set as near as is practical above the injection interval.
- d) Continually measure and record the wellhead casing and tubing pressures electronically.
- e) Cease injection and notify the Commission immediately if hydraulic isolation is lost in the wellbore or formation.
- f) Submit the annual packer isolation test report to the Commission within 30 days of the completion of the test.
- g) Include the disposal operating hours and the maximum injection pressure value on the monthly BC-S18 disposal statement.
- h) Conduct an annual reservoir pressure test on the formation in the subject well using bottom-hole recorders, with a shut-in period of sufficient length to provide data for calculation of the reservoir pressure, and submit a report of the test within 60 days of the end of the test.
- i) Cease injection upon reaching a maximum formation pressure of 5,300 kPaa, measured at 719 mKB.
- j)
  - i) Perform a casing inspection log on the subject well and submit results to the Commission within 30 days of the completion of logging, at an interval of not more than every 10 years, commencing from the date of initial disposal.
  - ii) Perform a hydraulic isolation temperature log on the subject well and submit results to the Commission within 30 days of the completion of logging, at an interval of not more than every 5 years.
- k) Not conduct a hydraulic fracture stimulation on any formation in the subject well without prior Commission approval.
- l) Implement a groundwater monitoring program as detailed in Appendix A.

  
\_\_\_\_\_  
Ron Stefik, Eng.L.  
Supervisor, Reservoir Engineering  
Oil and Gas Commission

DATED AT the City of Victoria, in the Province of British Columbia, this 23<sup>rd</sup> day of March, 2017.

## Advisory Guidance for Order 08-02-001 Amendment #1

- I. A production packer must be set above the injection interval and the space between the tubing and casing filled with corrosion and frost inhibiting fluids, as per section 16(2) of the Drilling and Production Regulation.
- II. Annual packer isolation tests are required to be submitted, as per section 16(3) of the Drilling and Production Regulation.
- III. Injected fluids must be metered and the injection pressure measured at the wellhead, as per section 74 of the Drilling and Production Regulation.
- IV. A monthly disposal statement must be submitted to the Commission not later than the 25<sup>th</sup> day of the month following the reported month, as per section 75 of the Drilling and Production Regulation.
- V. Seismic events must be reported and disposal operations suspended as per section 21.1 of the Drilling and Production Regulation.

**Appendix A – Groundwater Monitoring Requirements**

**ECA ECOG Etsho b-A90-J/94-O-02 (WA 23605) Produced Water Disposal**

1. One groundwater monitoring well shall be installed by December 31, 2017 within 50 m of the disposal well. The monitoring well shall be installed to a depth within the saturated groundwater zone, below the water table, to enable the collection of representative samples of groundwater from the well, to a maximum depth of 30 m.
2. During drilling of the monitoring well, geological conditions shall be logged.
3. A minimum of one representative “reference” groundwater sample shall be collected from the monitoring well following installation and appropriate development/purging.
4. The sample shall be submitted for laboratory analysis for analytical parameters including:
  - Major Cations and Anions (HCO<sub>3</sub>, CO<sub>3</sub>, SO<sub>4</sub>, NO<sub>2</sub>, NO<sub>3</sub>, Cl, Ca, Mg, K, Na, Fe, Mn)
  - Total Dissolved Solids (TDS)
  - Alkalinity
  - pH
  - Electrical Conductivity
  - Hardness
  - Dissolved Metals
  - Dissolved Gases (C1-C3)
  - Benzene, Ethylbenzene, Toluene, Xylenes (BETX)
  - Volatile Hydrocarbons (VH<sub>w</sub>) (C6 to C10)
  - Volatile Petroleum Hydrocarbons (VPH<sub>w</sub>) (C6 to C10 - BETX)
  - Extractable Petroleum Hydrocarbons C10-C19 (EPH<sub>w10-19</sub>)
5. The static water level shall be measured following development/purging and prior to sampling.
6. A reference groundwater monitoring report shall be submitted to the Commission within 60 days of the date of groundwater sampling. The report, pdf format, shall include: a graphical monitoring well log showing construction details and geological conditions, a site plan showing the location of the monitoring well relative to the disposal well and other site infrastructure, documentation of the UTM coordinates of the monitoring well (NAD1983) and monitoring well top elevation, descriptions of the procedures used in drilling and installing the monitoring well and for sampling, record of the measured static water level in the well, tabulated analytical results, and the laboratory analytical report.

7. Long term monitoring shall involve the collection of one representative groundwater sample from the monitoring well on an annual basis, and analysis for the following parameters:
  - Major Cations and Anions ( $\text{HCO}_3$ ,  $\text{CO}_3$ ,  $\text{SO}_4$ ,  $\text{NO}_2$ ,  $\text{NO}_3$ , Cl, Ca, Mg, K, Na, Fe, Mn)
  - Total Dissolved Solids (TDS)
  - Alkalinity
  - pH
  - Electrical Conductivity
  - Dissolved Metals
  - Dissolved Gases (C1-C3)
8. Annual sampling shall commence one year after the collection of the reference groundwater sample. The analytical results shall be submitted to the Commission annually within 60 days of sample collection by eSubmission, if available, or by Email to [Hydrogeology@bcogc.ca](mailto:Hydrogeology@bcogc.ca). Long term groundwater monitoring shall be implemented over the period extending from the date of reference groundwater sampling until one year after ceasing disposal and until authorized by the Commission.
9. Monitoring well installation and groundwater sampling procedures for this program shall be consistent with standard practices for environmental investigations such as those outlined in the British Columbia Field Sampling Manual (2013)  
[http://www2.gov.bc.ca/assets/gov/environment/research-monitoring-and-reporting/monitoring/emre/field\\_sample\\_man2013.pdf](http://www2.gov.bc.ca/assets/gov/environment/research-monitoring-and-reporting/monitoring/emre/field_sample_man2013.pdf)
10. At any time during this program, the Commission may require re-sampling to confirm a result or further investigation which may include additional sampling and/or additional analytical requirements.